



Jeio Tech 14 Litre Compact Low Temperature Incubator (ILP-02)

Product Code: 24032

Brand: Jeio Tech

The Jeio Tech 14 Litre Compact Low Temperature Incubator (ILP-02) is compact, lightweight, stackable, energy-efficient and offers exceptionally reliable low temperature incubation with the use of quiet peltier cooling technology, which prevents vibrations and a small generation of heat.

This low temperature incubator is ideal for growing microorganisms in life sciences, pharmaceuticals, clinical science, antibody testing, paraffin histochemical procedures, tissue culturing, crystalisation studies, and other applications in chemistry and biology.

RS-232 interface and Lab Tracer software available.



Performance:

- Temperature range from 10°C to 40°C. Contrary to conventional compressor-cooled incubators, peltier cooling technology generates little vibration, noise, and heat.
- Microprocessor PID control/auto-tuning/temperature calibration.
- Adjustable three-step fan speed with defrosting time/period control.

Convenience:

- Space saving design allows this unit to hold two 1000ml Erlenmeyer flasks.
- Intuitive control panel with bright LED display (0.1°C resolution).
- Dual delayed on/off timer modes (1 min. to 99 hr.. 59 min.).
- Convenient preset function for 3 most commonly used temperature settings.
- Up to 9 temperature steps and maximum 200 cycles of repetition programmable for each profile.
- Convenient sample monitoring without affecting the chamber's temperature via the inner tempered glass door.
- Corrosion-resistant incoloy sheath heating element and stainless steel interior.
- Environment-friendly insulation material (EPDM) used for safety and convenience (compliant with ASTM-C534 specification).
- RS-232 interface for external control and data collection.

Safety:

- Automatic run after power interruption.
- Keypad lock function prevents accidental changes during operation.
- Over-temperature and over-current protection.



Specifications:

Chamber Volume (litres)		14
Temperature	Range at 25°C	10 to 40
	Fluctuation at 25°C	± 0.1
	Variation at 25°C	± 0.5
Dimensions	Internal (w x d x h)	315 x 200 x 230mm
	External (w x d x h)	430 x 495 x 400mm
	No. of Wire Shelves (standard/max.)	1/5
	Net Weight (kg)	27.5
Electrical Requirements (230V)		50 Hz, I.8A

Unit 3, Tower Business Park Warpsgrove Lane Chalgrove Oxfordshire OX44 7XZ

Tel: (+44) 01865 400321

Email: enquiries@medlinescientific.com **Website:** www.medlinescientific.com