

Medline 20 Litre Chamber Furnace (MDUI200)

Product Code: MDUI200

Brand: Medline Scientific

Medline's 20 Litre Chamber Furnaces (MDUI200) has a maximum operating temperature of up to 1100°C.

This laboratory furnace has a simple lift-up door with a tight closing mechanism, and its chamber walls are built with insulating fire bricks to avoid mechanical abrasion, thermal aging, and deformation.

Features:

- Chamber walls made up of insulating fire bricks against mechanical abrasion and thermal aging and deformation.
- Half buried heaters in two sides and on top (housed in quartz tubes).
- Tight door closing mechanism.
- Homogeneous temperature gradient in the chamber thanks to similar heat loss in every direction.
- Optimal insulation thickness to reduce the temperature of the outer surface.
- Contactless outer shell for low surface temperature.
- Ergonomic PID control unit placement.
- Standard chimney with fan.
- Adjustable foot screw.
- Lift-up door allows different spatial use of applications.



Specifications:

Volume (litres)	20
Continuous Working Temperature (°C)	1075
Max. Temperature (°C)	1100
Chamber Dimensions (mm)	250 x 200 x 400
Power (W)	4000
I Max. (A)	19
Dimensions (w x d x h)	500 x 640 x 720mm
Weight (kg)	80

Unit 3, Tower Business Park
Warpsgrove Lane
Chalgrove
Oxfordshire
OX44 7XZ

Tel: (+44) 01865 400321

Email: enquiries@medlinescientific.com

Website: www.medlinescientific.com