

Priorclave 200 Litre Front Loading Autoclave, Electric

Product Code: MDPS/QCS/EH200

Brand: Priorclave

The Priorclave 200 Litre Front Loading Autoclave, Electric is one of the most versatile and cost efficient steam sterilisers available today. Offering 20% more loading capacity than other sterilisers of the same capacity, this laboratory autoclave has the flexibility to accommodate both small and taller than usual items, avoiding the need to invest in larger, heavier and more costly rectangular sterilisers.

From simple cycles to fully featured multi-programme operation with printed records, a powerful TACTORAL®2 controller allows unrivalled flexibility and monitoring. For a busy working environment, automating the sterilising process and with features to assist in autoclave management, TACTORAL®2 enables other tasks to be undertaken secure in the knowledge that sterilisation is proceeding safely and efficiently.

Introducing this Priorclave Front Loading Autoclave model to any laboratory will enable it to improve throughput brought about by the increased loading capacity and performance, as well as benefiting from lower overall running costs.



Features:

- Quick seal single-action door fitted with thermal and pressure locks to prevent opening at load temperature above 80°C and pressures above 0.2 bar.
- Tactrol 2 microprocessor control with simple and fully variable setting of process time, temperature with graphic indication of cycle status.
- Automatic timed free-steaming.
- Pre-cycle vacuum in which multiple vacuum stages are programmed with interspersed heating to achieve steam penetration (optional).
- Pulsed free steaming to maximise efficiency of pre-cycle vacuum phase (optional).
- Vacuum assisted cooling (optional).
- Low water level sensor.
- Post cycle drying for faster load drying. (optional).
- Two full width stainless steel load shelves.
- Epoxy coated panels and frame members are treated with an anti-bacterial agent which is effective against all bacteria and fungi including MRSA.
- Pressure vessel carries a 10 year warranty and is insurance approved.
- Service and support direct from manufacturer (or appointed distributor).

Specifications:

Autoclave Capacity (litres)	200
Chamber Size	500 x 1025mm
Chamber Material	Polished 316 stainless steel
Loading Format	Front
Loading Height	860mm
Operating Range	Up to 140°C, 2.4 bar
Heater Power	7kW at 30A; 10.5kW at 15A
Weight (kg)	236
External Dimensions (w x d x h)	740 x 1385 x 1535mm
Minimum Dimesnons (a x b x c)	1565 x 935 x 625mm

Unit 3, Tower Business Park
Warpsgrove Lane
Chalgrove
Oxfordshire
OX44 7XZ

Tel: (+44) 01865 400321

Email: enquiries@medlinescientific.com

Website: www.medlinescientific.com

* installation dimensions include space for doors to open fully and for pipes, etc. at the rear of the autoclave.

Consideration should be given to allow access for routine servicing.

