

## Jeio Tech 20 Litre Refrigerating & Heating Bath Circulator (RW3-2025P)

**Product Code:** AAH57662K

**Brand:** Jeio Tech

The Jeio Tech 20 Litre Refrigerating & Heating Bath Circulator (RW3-2025P) provide rapid heating and cooling throughout its entire temperature range.

Its seamless, round-cornered stainless steel tank with an accessible drain valve can be easily cleaned and ensure stability. With an optimum refrigeration system, samples and applications can be cooled quickly.

### Features

#### Performance

- Temperature range from  $-25^{\circ}\text{C}$  to  $150^{\circ}\text{C}$
- Optimum refrigeration system by microprocessor PID control. Energy efficient refrigeration operation is available within full range of temperature control
- Three point temperature calibration/automatic tuning/automatic run
- Suitable for both internal and external bath environments due to reduced turbulence by using five-speed adjustable pump and built-in cooling coil (1 to 3 steps of the pump for internal circulation and 4 to 5 steps for external circulation)

#### Convenience

- Bright VFD display with quick adjustable dial knob ( $0.1^{\circ}\text{C}$  resolution)
- Dual wait on/off timer modes (1 min. to 99 hr. 59 min.)
- Convenient memory function of up to three most frequently set temperatures
- Corrosion-resistant, leak-proof, round-cornered, and easy-to-clean stainless steel bath with front access drain valve
- Detachable condenser air-filter for easy maintenance of refrigerating efficiency
- CFC-free refrigerant (R-507, R-404A) and a double service valve for leakage prevention
- Quick-release front grill for easy cleaning of the condenser
- Built-in RS-232 port and USB port for external control and data collection
- Side handles enable convenient handling and transport

#### Safety

- Isolated design of agitator, heater, and sensor by a baffle plate minimising the turbulence in the bath fluid and also to protect users and samples against direct contact
- Complete safety precaution system with warning alarms (low fluid level and dry-running, over-temperature, over-current)
- Keypad lock function prevents accidental changes during operation



## Specifications

<b>Bath Volume (L)</b>		20
<b>Temperature Range (°C)</b>		-25 to 150
<b>Temperature Accuracy (°C)</b>		± 0.05
<b>Cooling Capacity (Bath Fluid: Ethanol)</b>	<b>At -20°C</b>	310
	<b>At 0°C</b>	610
	<b>At +20°C</b>	850
	<b>Refrigerator</b>	1/2 LBP, R-404A
<b>Pump Pressure (PSI)</b>		5.9
<b>Pump Flow Rate (l/min.)</b>		28
<b>Dimensions (W x D x H)</b>		386 x 602 x 825mm
<b>Weight (kg)</b>		60

Unit 3, Tower Business Park  
Warpsgrove Lane  
Chalgrove  
Oxfordshire  
OX44 7XZ

**Tel:** (+44) 01865 400321

**Email:** [enquiries@medlinescientific.com](mailto:enquiries@medlinescientific.com)

**Website:** [www.medlinescientific.com](http://www.medlinescientific.com)