

Jeio Tech 302 Litre Floor Standing Temperature & Humidity Chamber (TH-KH-300)

Product Code: AAHC3112K

Brand: Jeio Tech

The Jeio Tech 302 Litre Floor Standing Temperature & Humidity Chamber (TH-KH-300) has a wide temperature range that goes down to -70°C , along with highly advanced features for quality and reliability.

Features:

Performance:

- Microprocessor PID control/temperature calibration/automatic tuning.
- Advanced performance of low and high temperature and humidity control, achieved by adapting the humidification tank exterior to the chamber, added benefit for long term test.
- Water recycling and filtering system reduce water consumption for longer operation.
- Air-tight door closure with perfect sealed packing. Heat-resistant silicone packing completely blocks high heat leakage from the inner chamber. Two-point door latch also enhances tightness to door closure.
- Energy efficiency is achieved by optimisation of the insulation system. Even if the unit is operating at max. temperature, the surface of the unit doesn't allow high temperatures of over 60°C .

Safety:

- Built in door lock with a key.
- Automatic shut off after overheat alarm.
- Low and empty water level alarm.
- Power supply leakage breaker.
- Over current protection.
- Open door alarm.

Convenience:

- Corrosion resistance stainless steel chamber and electric polished humidification tank.
- Maintenance of water supply are easily performed with a front water tank. Portable water container makes supplying water convenient.
- Water supply during operation is also available for long term test purposes.
- Direct water system provides user great convenience when performing long-term tests (optional).
- Clear observation of samples. Tempered glass door with built in heating wire. Energy efficient, long life span LED lighting. Wider view, inner glass door is available for monitoring of samples (optional).
- Cable port for introduction of external probes or wires. 50mm diameter cable port comes standard on the left side of the unit. Additional 50mm or 80mm diameter cable ports, custom ordered (optional).
- Casters for easy mobility during installation or relocation.
- User friendly LCD controller. 5.7 inch colourful interactive touch type LCD controller. Set value and present value are clearly visible together on display. Operating progress visible in graph mode allow for direct data interpretation. Built in SD card drive. Trilingual support (English/Chinese/Korean). Temperature and other operating parameters recorded with use of selectable recorder (optional). Sufficient programmable control support.
- Computer interface. RS-485 communication port enables connection of up to maximum 9 units. Simultaneous monitoring and operating of multiple units is an available feature (optional). Programme patterns are simple to set with the use of our software. Storage of programme information, back-up of value settings, recovery, temperature, humidity values. RS-232 communication port comes standard.



Specifications:

Chamber Volume (litres)		302	
Controller		Programmable, touch screen type controller (5.7" colour monitor)	
Temperature	Range	Without Humidity (°C)	-70 to 150
		With Humidity (°C)	15 to 90
	Fluctuation at 40°C/ 75%RH		± 0.3
	Variation at 40°C/ 75%RH		± 0.5
Time (min.)	Heating without Humidity		70 from -70°C to 120°C
	Cooling without Humidity		80 from 20°C to -70°C
Humidity	Range (%RH)		20 to 95
	Fluctuation at 75%RH/40°C		± 0.4
	Variation at 75%RH/40°C		± 3
Refrigeration	System		Mechanical dual stage refrigerator system (air-cooled condenser)
	Refrigerant		R-507, R-23
Water Supply	Capacity (litres)		15
	Water Quality		pH 6.2 to 7.2/electrical conductivity 20µs/cm to below
No. of Wire Shelves (standard/max.)		2/10	
Distance of Between Shelves (mm)		60	
Max. Load Per Shelf (kg)		25	
Permitted Total Load (kg)		65	
Dimensions	Internal (w x d x h)		600 x 630 x 800mm
	External (w x d x h)		1150 x 1615 x 1760mm
	Viewing Windows		200 x 330mm
	Net Weight (kg)		385
Cable Port		Basically one hole provided/ Ø 50mm. Optionally max. two holes available/Ø 50mm or 80mm.	
Interface Port		Basically RS-232C (RS-485 optional).	

Unit 3, Tower Business Park
 Warpsgrove Lane
 Chalgrove
 Oxfordshire
 OX44 7XZ

Tel: (+44) 01865 400321

Email: enquiries@medlinescientific.com

Website: www.medlinescientific.com