



LSFSR47DC-UK 47L Laboratory Refrigerator, Solid Door

LSFSR47DC-UK

- ✓ New updated Controller system for improved user experience. Read, Record, Reset simply with the touch of one button, with no stress of accidentally resetting on the clear digital display.
- ✓ Porthole - Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.
- ✓ Flexible internal storage- Multiple shelf locations along with a wire basket provides a flexible storage solution.
- ✓ Anti-microbial handle -Powder coated to help prevent cross contamination by inhibiting the growth of microbes.
- ✓ Spark-free - Will have items removed such as fans and lights so the interior of the fridge has no chance of igniting flammable liquids.

SPECIFICATION

Dimensions	475mm x 445mm x 565mm
Weight	17.5kg
Gross Capacity (Litres)	47 Litres
Net Capacity (Litres)	30 Litres
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm)	565mm
Product Weight (kg)	17.5kg
Packed Width (mm)	490mm

Packed Depth (mm)	530mm
Packed Height (mm)	620mm
Packed Weight (kg)	21.5kg
Country Of Origin	UK
Internal Dimensions (mm) (WxDxH)	403mm x 354mm x 425mm
Temperature Range	+2°C to +10°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type Of Plastic	SRL800 (HIPS/ABS Mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Open Depth (mm)	905mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet	2, Front Adjustable
Porthole	Yes
Porthole Size (mm)	16mm
Porthole Location	Rear LH Corner
Temperature Display On Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number Of Shelves	1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	416mm x 200mm x 6mm
Shelf Material	Polythene Coated Wire

Number Of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	396mm x 165mm x 150mm
Interior Light	No
Fan	No
Spark Free	Yes
Defrost Setting	Auto (Off Cycle)
Controller Type	Digital External
Number Of Probes	1
Probe Type	Air
Ambient Temperature Range	+10°C to +32°C
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply (V)	220-240V
Insulation Thickness (mm)	40mm
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes
Wall Brackets	Yes
Optional Drawer System	No
Optional Digital Lock	No
Other Door Option	No