Funnel Shaker



















Powerful up-down reciprocal motion

Structural Functional Features

- · Vertical reciprocation at a maximum of 300 rpm.
- · 40 mm stroke length.
- $\cdot\,$ Adjustable shake tilt (0~20°) to achieve high mixing efficiency at low rpm.
- · Count-down timer. (up to 999 hours and 59 minutes)
- · 5kg on one side, 10kg in total.
- · Convenient holder height adjustment.
- · Stable device structure at high speeds.

Use Convenience Features

- · Digitally displays up-down reciprocal motion and it's easy to adjust speed with dial.
- Easy to detach separated funnel, maximizing convenience for repeat users.
- · Adjustable height of funnel holder makes it possible to mount funnels of various sizes. (up to 2L)
- 4 holders are provided as basic,
 10 holders can be mounted in maximum when it adds.
 (option, but the available mounted quantities are depends on the funnel size.)
- · Monitor via mobile app anytime, anywhere with LC Connected. (mobile monitoring system) (when purchased LC GreenBox)

Outstanding Safety

- · Alarms occur when there is a deviation between set rpm and actual rpm.
- · Over-current protection.
- · Optimized balance design to use in stable even when samples are installed at one side or tilted reciprocal motion.
- \cdot Automatic restart in the event of sudden power loss.



RS-2 with Holders 4ea (standard), Holders 2ea (option)



Up to 5 holders may be installed on each side.



Tilt angle adjustment from 0 to 20° for maximum mixing efficiency.

Specification

Model	RS-2	
Shaking system		
Motion type	Vertical & Inclined reciprocating (0 ~ 20°)	
Speed range (rpm)	Vertical 30 to 300 / Inclined 30 to 250	
Speed accuracy at 100rpm (± rpm)	1	
Amplitude, recip. stroke length (mm / inch)	40 / 1.6	
Timer	999hr 59 min	
Dimension		
Exterior (W x D x H, mm / inch)	600 x 460 x 470 / 23.6 x 18.1 x 18.5	
Minimum required space considering 20° tilt	900 x 460 x 670 / 35.4 x 18.1 x 26.3	
Max. load per each side (kg / lbs)	5 / 11	
Net weight (kg / lbs)	52 / 114.6	
Electrical data & Ordering No.		
100 ~ 240V, 50/60Hz, A	0.9 Max.	
Cat. No.	AAH32025K	

Maximum number of installed funnels (per side)

11 /		
Funnel Capacity	Round type	Cylindrical type
Less than 500 mℓ	3 - 5ea	3 - 5ea
500 mℓ	3ea	3ea
1L	3ea	3ea
2L	2ea	2ea

Accessories

Cat. No.	Description
AAA32502-V1	Funnel holder
AAHQ1011K	LC GreenBox